

REQUEST FOR MODIFICATION OF BUILDING ORDINANCES

UNDER AUTHORITY OF L.A.M.C. SECTION 98.0403

PERMIT APP. #:	DATE:		
JOB ADDRESS:			
Tract:	Block:		
	Lot:		
Owner:	Petitioner:		
Address:	Address:		
City State Zip Phone	City State Zip Phone		
REQUEST (SUBMIT PLANS OR ADDITIONAL SHEETS AS NECESSARY)	CODE SECTIONS: L.A.M.C. 94.401.0; 94.301.1.1		
Request to install and maintain concrete floor troughs instead	of approved waste piping as required by code.		
ILICTIFIC ATION (corporation)			
JUSTIFICATION (SUBMIT PLANS OR ADDITIONAL SHEETS AS NECESSARY			
This is a practical means of handling waste water in this type of	or installation. No insanitary conditions are anticipated.		
Owner/Petitioner Name (Print) (Signature)	Position		
FOR CITY DEPARTMENT'S L	JSE ONLY BELOW THIS LINE		
Concurrences required from the following Department(s)	Approved Denied		
Los Angeles Fire Department Print Name			
Public Works Bureau of Engineering Print Name			
Department of City Planning Print Name	Sign		
Department of County Health Print Name	Sign		
Other Print Name	Sign L		
DEPARTMENT ACTION			
Reviewed by: (Staff) (print)	Sign Date		
GRANTED DENIED			
Action taken by: (Supervisor) (p	rint) Sign Date		
NOTE: IN CASE OF DENIAL, SEE PAGE #2	OF THIS FORM FOR APPEAL PROCEDURES		
CONDITIONS OF APPROVAL (Continued on Pag	ge 2): For Cashiers Use Only (PROCESS ONLY WHEN FEES ARE VERIFIED)		
<u> </u>	(PROCESS ONLY WHEN FEES ARE VERIFIED)		
(See Attached Conditions of Approval on Pag	70.3)		
(See Attached Conditions of Approval on Fat	ge 3)		
FEES			
Appeal Processing Fee (No. of Items) = 1 x \$130 + \$39/addl	= <u>130.00</u>		
Inspection Fee(No of Insp.) = 1 X \$ 84.00	=84.00		
Research Fee (Total Hours Worked) = 1 X \$104.00	= 104.00		
Subtotal	= 318.00		
Surcharge (One Stop)	=		
Total Fees	= 19.08 H		
	= <u>19.08</u> = 343.44		
	= 19.08 $= 343.44$		
Fees verified by:	$= \frac{19.08}{343.44}$		
	=343.44		

CONDITIONS OF APPROVAL (Continued from Page 1)				
(See Attached Conditions of Approval on Page 3)				
	_			

Job Address:

CITY OF LOS ANGELES BOARD OF BUILDING AND SAFETY/DISABLED ACCESS COMMISSION APPEAL FORM

(Must be Attached to the Modification Request Form, Page 1)

AFFIDAVIT - LADBS BOARD OF E	BUILDING AND SAFE	TY COMMISSION	ERS – RESOLUTION NO. 832-9	3	
(Print or Type Name of the Person Signing this Form) The name and mailing address of the over	do state and swea	r as follows:			
 (Print or Type Name of the Person Signing this Form) The name and mailing address of the ov the appeal application (LADBS Com 31) 	mor or the property (as dominat	d in the resolution 832-93	s) at	_ as shown on	
2. The owner of the property as shown on t	the appeal application will be n	nade aware of the appea	I and will receive a copy of the appeal.		
I declare under PENALTY OF PERJURY that the fo	0 0				
Owner's Name(s)					
			Please Type or Print		
Owner's Signature(s)	ner's Signature(s) (Tw		(Two Officers' Signatures Required for Corporations)		
	riease Sigit				
Name of Corporation(Please Print	: Name of Corporation)		(Please Type or Print)		
Dated this day of		20	_		
CALIFORNIA ALL-PURPOSE ACKNO					
State of CALIFORNIA					
	_				
before me,Name, Title of Officer (e.g. Jane	Doe, Notary Public)	<u></u>	Name(s) of Signer(s)	,	
certify under PENALTY OF PERJURY under the foregoing is true and correct. WITNESS my hand and official seal.	raws of the state of Camon	Signatu	re		
	ARTMENT ACTION TO		BUILDING AND SAFETY		
	SIONERS/DISABLED				
Applicant's Name		A	oplicant's Title		
Signature			ate		
FEES			For Cashiers Use Or		
Board Fee(No. of Items)	x \$130.00	= 0.00	(PROCESS ONLY WHEN FEES ARE	VERIFIED)	
Inspection Fee(No of Insp.) =	· ·	= 0.00			
Research Fee (Total Hours Worked) =	X \$104.00	= 0.00			
Subtotal		=0.00			
Surcharge (One Stop)	X 2%	= <u>0.00</u>			
Surcharge (Systems Development)	X 6%	= 0.00			
Total Fees		=0.00			
Fees verified by:					
Print and Sign					
i iiik and Olgii					

Permit App #:

SUPPLEMENTAL INFORMATION AND/OR SKETCH OF JOB CONDITION

BASIS FOR APPROVAL-INFORMATION

INFORMATION ON PROCEDURE FOR APPEAL FROM A DETERMINATION OR ACTION BY THE DEPARTMENT OF BUILDING AND SAFETY

For the Superintendent of Building or his designated agent to approve a request for modification or a request for alternate material or method of construction he must determine that special, individual reasons exist that make compliance with the strict letter of the ordinance impractical and that equivalency is provided for requests applicable to the State Housing Law. The resulting condition must be in conformance with the spirit and purposeof the ordinance involved. The applicant must provide sufficient information with this application to allow the above evaluation to be made.

Appeal from the determination or action of the Superintendent of Building or his designated agency may be made to the Board of Building and Safety Commissioners. To appeal, the appellant must give special individual reasons that make compliance with the strict letter of the ordinance impractical. Appeals pertaining to State Housing Law provisions require complete evidence to substantiate that the proposed design, material, or method of construction is at least equivalent to that prescribed by the Code. State such reasons or evidence on the front of this form or on a separate attachment.

DATE:

JOB ADDRESS:

CONDITIONS OF APPROVAL FLOOR TROUGHS

- 1. Obtain a Plumbing Permit for the installation of the floor trough.
- 2. Floor troughs shall not be less than four (4) inches in width and shall maintain a minimum of 1% slope to an approved floor drain located in the bottom of the trough.
- 3. Walls and bottom of trough shall be at least four (4) inches thick Class"C"concrete. Sides and bottom shall be reinforced with #3 longitudinal steel reinforcing bars placed at mid-thickness of the concrete, and not less than one bar for each side placed not less than three (3) inches nor more than six (6) inches from top and sides with an additional bar for each two (2) feet of depth of trench.

The bottom shall be reinforced with not less than one #3 longitudinal steel reinforcing bar placed at center of bottom with an additional bar for each two (2) feet of width of bottom.

Minimum #2 bar U-Stirrups shall be placed not less than three (3) feet center to center.

In lieu of the above, reinforcing may consist of cold-drawn welded steel reinforcing fabric 6" x 6" x #10 x #10 placed mid-thickness of concrete. Structural design and approval shall be provided at locations where structural integrity may be compromised.

- 4. Troughs shall be troweled smooth with cement plaster having a waterproof additive.
- 5. Changes in direction of the trough shall be accomplished by the use of long radius design.
- 6. The junction between the trough walls and bottom shall be rounded with a cove of at least three-eights (3/8) inch radius.
- 7. No trough shall be placed under any fixed equipment unless the bottom of such equipment is at least 12 inches above the floor surface.
- 8. Trough drains being discharged to the sanitary system shall be properly trapped and vented.
- 9. Troughs shall be covered with solid metal covers or grating, and when subject to vehicular traffic shall be provided with traffic rated grating.
- 10. An approved floor drain shall be properly installed at the bottom of the trough.